

**Amendments to the Claims:**

Please cancel claims 1-17 as being drawn to a non-elected invention. Please amend claims 18 and 22-24 as follows. Please add new claims 26-47 as follows.

This listing of claims replaces all prior versions, and listings, of claims in the application.

**Listing of claims:**

1.-17. (canceled)

18. (currently amended) A fluid dispensing tip comprising  
an elongated ~~cylindrical~~ neck;  
a ~~cylindrical~~ bore machined in the neck along a ~~centered at the~~ longitudinal axis of the neck, the ~~cylindrical~~ bore having a cylindrical input end at an input end of the neck and a cylindrical output end at an output end of the neck, the output end of the bore having an outlet through the output end of the neck;  
the said cylindrical input end of the said bore having a first inner diameter and the said cylindrical output end of the said bore having a second inner diameter, the first inner diameter being greater than the second inner diameter;  
an inner taper machined in the bore between the cylindrical input end and the cylindrical output end for transitioning the inner surface of the bore from the first inner diameter to the second inner diameter, the inner taper being proximal to the output end of the neck; and  
outlet vents in at the output end of the neck, the outlet vents extending radially from the ~~fluid-path~~ outlet.
19. (original) The fluid dispensing tip of claim 18 wherein the outlet vents each comprise a V-groove having first and second inner surfaces.
20. (original) The fluid dispensing tip of claim 19 wherein the first and second inner surfaces of the V-groove intersect at an angle ranging between 45 degrees and 135 degrees.

21. (original) The fluid dispensing tip of claim 18 wherein the outlet vents are treated by a finishing process that reduces surface tension.
22. (currently amended) The fluid dispensing tip of claim 18 wherein the output end of the neck dispense tip includes a relieved outer surface.
23. (currently amended) The fluid dispensing tip of claim 18 wherein the output end of the neck dispense tip includes a beveled outer surface.
24. (currently amended) The fluid dispensing tip of claim 23 [[18]] wherein the beveled outer surface bevel is ground substantially along the longitudinal axis of the neck such that any tooling marks resulting therefrom are substantially aligned with the longitudinal axis.
25. (original) The fluid dispensing tip of claim 18 wherein the vents are ground substantially along their longitudinal axes such that any tooling marks resulting therefrom are substantially aligned with the longitudinal axes of the vents.
26. (new) The fluid dispensing tip of claim 18 wherein the outlet is located at a central position of the output end of the neck.
27. (new) The fluid dispensing tip of claim 18 wherein the outlet is in communication with the outlet vents.
28. (new) The fluid dispensing tip of claim 18 wherein the dispensing tip is unitary.
29. (new) The fluid dispensing tip of claim 28 wherein the dispensing tip is machined from stock.

30. (new) The fluid dispensing tip of claim 18 wherein the outlet vents comprise grooves in an outer surface of the output end of the neck.
31. (new) The fluid dispensing tip of claim 18 wherein the neck is cylindrical.
32. (new) A fluid dispensing tip comprising:  
an elongated cylindrical neck;  
a cylindrical opening in the neck along a longitudinal axis of the neck, the cylindrical bore having a cylindrical input end at an input end of the neck and a cylindrical output end at an output end of the neck;  
the cylindrical input end of the bore having a first inner diameter and the cylindrical output end of the bore having a second inner diameter, the first inner diameter being greater than the second inner diameter;  
an inner taper machined in the bore between the cylindrical input end and the cylindrical output end for transitioning the inner surface of the bore from the first inner diameter to the second inner diameter, the inner taper being proximal to the output end of the neck; and  
outlet vents at the output end of the neck, the outlet vents extending radially from the fluid path, wherein the vents are ground substantially along their longitudinal axes such that any tooling marks resulting therefrom are substantially aligned with the longitudinal axes of the vents.
33. (new) A fluid dispensing tip comprising:  
an elongated neck;  
an elongated fluid path in the neck along a longitudinal axis of the neck, the fluid path having an input at an input end of the neck and an output at an output end of the neck, the output of the fluid path having an outlet that passes through the output end of the neck;  
the input of the fluid path having a first inner diameter and the output of the fluid

path having a second inner diameter, the first inner diameter being greater than the second inner diameter;

an inner taper in the fluid path between the input and the output of the fluid path for transitioning the inner surface of the fluid path from the first inner diameter to the second inner diameter, the inner taper being proximal to the output end of the neck; and

outlet vents in the output end of the neck, the outlet vents extending radially from the outlet of the fluid path, wherein the dispensing tip is unitary between the input end of the neck and the output end of the neck.

34. (new) The fluid dispensing tip of claim 33 wherein the fluid path input is circular in cross section and wherein the fluid path output is circular in cross section.
35. (new) The fluid dispensing tip of claim 33 wherein the fluid path input is cylindrical in cross section and wherein the fluid path output is cylindrical in cross section.
36. (new) The fluid dispensing tip of claim 33 wherein the outlet vents each comprise a V-groove having first and second inner surfaces.
37. (new) The fluid dispensing tip of claim 36 wherein the first and second inner surfaces of the V-groove intersect at an angle ranging between 45 degrees and 135 degrees.
38. (new) The fluid dispensing tip of claim 33 wherein the outlet vents are treated by a finishing process that reduces surface tension.
39. (new) The fluid dispensing tip of claim 33 wherein the output end of the neck includes a relieved outer surface.
40. (new) The fluid dispensing tip of claim 33 wherein the output end of the neck includes a beveled outer surface.

41. (new) The fluid dispensing tip of claim 40 wherein the beveled outer surface bevel is ground substantially along the longitudinal axis of the neck such that any tooling marks resulting therefrom are substantially aligned with the longitudinal axis.
42. (new) The fluid dispensing tip of claim 33 wherein the vents are ground substantially along their longitudinal axes such that any tooling marks resulting therefrom are substantially aligned with the longitudinal axes of the vents.
43. (new) The fluid dispensing tip of claim 33 wherein the outlet is located at a central position of the output end of the neck.
44. (new) The fluid dispensing tip of claim 33 wherein the outlet is in communication with the outlet vents.
45. (new) The fluid dispensing tip of claim 33 wherein the dispensing tip is machined from stock.
46. (new) The fluid dispensing tip of claim 33 wherein the outlet vents comprise grooves in an outer surface of the output end of the neck.
47. (new) The fluid dispensing tip of claim 33 wherein the neck is cylindrical.